

DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc, Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused



1101-1110 DC Defender 48-5

Features

- UL 497B, Class I/Div II, ATEX
- 100% SASD Protection
- Screw Terminal Block
- Pole or Wall Mount

Applications

- Industrial Automation
- Controls & Sense Loops
- Telecommunications Base Stations
- IT & Data Centers
- Wastewater Treatment
- Rail
- Oil & Gas
- LED Lighting

Description

DC surge protector (also known as SPD or lightning protector) 1101-1110 from Transtector is a UL 497B, Class I/Div II, ATEX Clamshell style SPD that utilizes state of the art SASD technology to protect critical equipment that operates on a 48 Vdc electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector DC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		48		Vdc
Current Rating			15	A
Maximum Continuous Operating Voltage (MCOV)				
MCOV DC			60	Vdc

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		
Surge Protection Modes		DC+ to DC-, DC+ to GND, DC- to GND		
Response Time			5	ns
8/20 μ s Surge Current			5	kA
VPL 8/20 μ s L-G			97 @ 500A	Vpk

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc, Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused 1101-1110](#)

DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc,
 Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused



1101-1110
 DC Defender 48-5

Mechanical Specifications

Size

Height	7.17 in	[182.12 mm]
Width	5.69 in	[144.53 mm]
Depth	1.65 in	[41.91 mm]
Weight	1 lbs	[453.59 g]
Housing Material and Plating	Aluminum	

Environmental Specifications

Temperature

Operating Range	-40 to +85 deg C
Storage Range	-40 to +85 deg C
Humidity	<95% non-condensing

Installation

Mount Type	Pole, Wall/Panel
Service Wiring Terminal Copper Lug	#14 to #10 AWG

Compliance Certifications

RoHS Compliant	Yes
CE Compliant	Yes
UL Compliant	Yes
ANSI Compliant	Yes
Hazardous Locations Certifications	Yes UL 497B CSA ETL 60950-1 EN 60079-0 EN 60079-15 Class 1 Zone 2 Ex nA IIC T4 Gc 60Vdc, 15A IP54 Class 1 Div 2 Groups A,B,C,D T4 Class 1 Zone 2 AEx nA IIC T4 Gc Class 1 Zone 2 Ex nA IIC T4 Gc

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc, Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused 1101-1110](#)

DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc,
Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused

1101-1110
DC Defender 48-5



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: [DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc, Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused 1101-1110](#)

URL: <https://www.transtector.com/dc-surge-protector-spd-dc-defender-outdoor-1101-1110-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc, Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused

1101-1110 CAD Drawing

REVISIONS		
REV.	DESCRIPTION	DATE
A	INITIAL RELEASE	1/17/19
		APPROVED DWR

5.69 [144.5]
3.44 [87.4]

7.15 [181.6]

1.65 [41.9]

POLE/WALL MOUNTING EARS WITH GROUND POSITIONS

2X 2-POS WAGO CAGE CLAMP CONNECTORS FOR IN/OUT SERVICE WIRING

2X LID REMOVAL SCREWS

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X±.2 [5.08]	FRACTIONS ±.1/32	ANGLES ±1°
XX±.01 [.25]		
XXX±.005 [.13]		

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

THIRD-ANGLE PROJECTION

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF TRANSTECTOR CORPORATION. ALL RIGHTS RESERVED.

TRANSTECTOR

10701 AIRPORT ROAD, HAYDEN, ID, 83835
PHONE: 1.208.635.6400 | 1.800.882.9110
FAX: 1.208.955.2041
www.transtector.com | e-mail: sales@transtector.com

SIZE: A CAGE: 30992 DRAWN BY: HMB PART NUMBER: 1101-1110 SHEET: 1 OF 1 SCALE: 1:3

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.