

# Wall Mount Outdoor Hybrid Enclosure



## Features

- NEMA 4X rating for harsh environment protection
- Gland sizes for range of cable diameters (5 mm - 44 mm)
- 24 Fiber (6 LC QUAD SM adapters)
- 12 (14-AWG to 4-AWG) Power Terminals
- Ground bus bar
- Stainless Steel Wall Mount

©2023 viaPhoton, Inc. All rights reserved.

## Outdoor Hybrid Enclosure with Power and Fiber Connectivity

# Specifications



Outdoor enclosure

PART NUMBER	OHE-24-6PN-G4	OHE-24-10PN-G4
Dimensions	15.5 in H x 13.6 in W x 7.72 in D 17 in H with glands	15.5 in H x 13.6 in W x 7.72 in D 17 in H with glands
Weight	12 lbs	13 lbs
Power Terminals	12 Terminals (6 Circuits)	20 Terminals (10 Circuits)
Fiber Adapter	6 LC Quad Adapter	6 LC Quad Adapter
Cable Gland Seal	Custom configuration for cable diameters (5 mm - 44 mm)	
Enclosure Material	Polymer, Ruggedized, UV Rated, Gray	



Customizable gland sealing

## STANDARD FEATURES

Mounting	Wall Mount
Enclosure Door	Hinged
Security	Stainless steel latch with padlock clasp
Outdoor Temperature Range	-40°C to +80°C (-40°F to +176°F)
Environmental, Sealing	NEMA 4X, IP 66
Instrumented Dart Impact	73°F, 565 in-lb.
Falling Ball Impact	73°F 900 in/lb. Test Spec. UL-746
Flame Rating	UL, 5VA. Test Spec. UL-94
Outdoor UV Exposure	F1. Test Spec UL

## PACKAGING INFORMATION

Packaging Quantity	1 unit / box
Shipping Box Size (in)	24 L x 18 W x 10 H
Packaging Weight	12.5 lbs (6PN) 13.5 lbs (10PN)



Wall Mount

Optional mount  
available  
Part # VP-PMKIT



©2023 viaPhoton, Inc. All rights reserved.